

Setup:Installation Guide/Webservices/PDF-Export

Contents

1 Tips for this Document	2
2 Copying the BShtml2PDF Application	2
3 Restart Tomcat	2
4 Activating the PDF Export in BlueSpice	2
5 Troubleshooting	4

This document describes the installation of the PDF export of BlueSpice. Please make sure that the [Apache Tomcat server](#) is completely installed and configured at the BlueSpice server.

Tips for this Document

- Please, read this manual completely and work through the single installation steps one after another.
- For editing the configuration files with a text editor, the files must be saved in UTF-8 coding without BOM (Byte Order Mark).
- The placeholder `<installpath-bluespice>` stands for the path to your BlueSpice installation, e.g. `C:\inetpub\wwwroot\bluespice` (Windows) or `/var/www/bluespice` (Linux).
- The placeholder `<tomcat-webapps>` stands for the path to the Webapps directory of your Tomcat server, e.g. `C:\Program Files\Apache Software Foundation\Tomcat 8.5\webapps` (Windows) or `/var/lib/tomcat8/webapps` (Linux).

Copying the BShtml2PDF Application

Move the file "BShtml2PDF.war" from the directory `<installpath-bluespice>/extensions/BlueSpiceExtensions/UEModulePDF/webservices` to `<tomcat-webapps>`

Restart Tomcat

Restart the Tomcat Webserver like described [here](#).

Activating the PDF Export in BlueSpice

Go to the directory `<installpath-bluespice>/extensions/BlueSpiceExtensions`. If the file **BlueSpiceExtensions.local.php** does not exist already, please copy the file **BlueSpiceExtensions.default.php** and place it in the same folder under the name **BlueSpiceExtensions.local.php**. Open this file in a text editor.

Scroll to the end of the file. You will find the following lines there:

```
#require_once( __DIR__."/UniversalExport/UniversalExport.setup.php" );  
#require_once( __DIR__."/UEModulePDF/UEModulePDF.setup.php" );
```

Remove the first character (#), save the file and exit it.

Open a command line and change to the `<installpath-bluespice>` folder. Execute the following command:

```
php maintenance/update.php (Linux)  
php maintenance\update.php (Windows))
```



In Windows, make sure that the **environment variables** are set correctly to access the php command.



Note that you must update the file system permissions after running update.php.

When the script is finished with the "Done" message, the web service is successfully installed.

```
...event_agent field does not exist in echo_event table, skipping modify field patch.
Modifying event_variant field of table echo_event ...done.
Modifying event_extra field of table echo_event ...done.
Modifying event_agent_ip field of table echo_event ...done.
...have etp_id field in echo_target_page table.
...have notification_bundle_base field in echo_notification table.
...echo_event table does not contain event_timestamp field.
...have eeb_event_hash field in echo_email_batch table.
...have event_page_id field in echo_event table.
...index echo_event_type already set on echo_event table.
...index echo_user_timestamp already set on echo_notification table.
Creating titlekey table...ok.
Rebuilding titlekey table...
... 1 ok.
...hitcounter table does not exist, skipping modify field patch.
Creating hit_counter_extension table ...done.
Creating hit_counter table ...done.
...page table does not contain page_counter field.
Creating bs_editnotifyconnector table ...done.
Creating bs_namespacemanager_backup_page table ...done.
Creating bs_namespacemanager_backup_revision table ...done.
Creating bs_namespacemanager_backup_text table ...done.
Adding page_content_model field to table bs_namespacemanager_backup_page ...done.
Adding rev_shal field to table bs_namespacemanager_backup_revision ...done.
Adding rev_content_model field to table bs_namespacemanager_backup_revision ...done.
Creating bs_permission_templates table ...done.
Creating bs_dashboards_configs table ...done.
Creating bs_usagetracker table ...done.
Creating bs_pagetemplate table ...done.
Creating bs_pageassignments table ...done.
...se_text field does not exist in bs_saferedit table, skipping modify field patch.
Creating bs_readers table ...done.
...have readers_ts field in bs_readers table.
...site_stats is populated...done.
Checking existence of old default messages...done.
Populating rev_len column
...doing rev_id from 1 to 200
Populating ar_len column
...archive table seems to be empty.
rev_len and ar_len population complete [0 revision rows, 0 archive rows].
Populating rev_shal column
...doing rev_id from 1 to 200
Populating ar_shal column
...archive table seems to be empty.
Populating ar_shal column legacy rows
rev_shal and ar_shal population complete [0 revision rows, 0 archive rows].
Populating img_shal field

Done 0 files in 0.0 seconds
Fixing protocol-relative entries in the externallinks table...
Done, 0 rows updated.
Populating fa_shal field from fa_storage_key

Done 0 files in 0.0 seconds
Updating *_from_namespace fields in links tables.
...doing page_id from 1 to 200
Purging caches...done.

Done in 1.6 s.
root@bluespice:/var/www/bluespice#
```

Troubleshooting

If there is a problem with PDF export in BlueSpice, first check the [file system permissions](#).