

## Setup:Installation Guide/Advanced/Configuration Folder settings.d

A [quality version](#) of this page, [approved](#) on *7 April 2017*, was based off this revision.

### Contents

<a href="#">1 Tip for theDocument</a> .....	<a href="#">2</a>
<a href="#">2 Explanation For the Folder settings.d</a> .....	<a href="#">2</a>

## Tip for the Document

---

- Please, read this manual completely and work through the single installation steps one after another.
- For editing the configuration files with a text editor, the files must be saved in UTF-8 coding without BOM (Byte Order Mark).
- The placeholder `<installpath-bluespice>` stands for the path to your BlueSpice installation, e.g. `C:\inetpub\wwwroot\bluespice` (Windows) or `/var/www/bluespice` (Linux).



**This document provides background information for advanced users. We recommend not to make any changes on BlueSpice, if you are not familiar with the following information.**

## Explanation For the Folder settings.d

---

Starting with BlueSpice version 2.27.1, all default settings as well as the modules of BlueSpice are outsourced. All configurations can now be found in separate files in the `<installpath-bluespice> /settings.d` folder.

The files in this folder integrate the standard MediaWiki extensions required for BlueSpice, perform recommended default configurations, and also integrate all BlueSpice-related extensions (free or pro).

The files in the `<installpath-bluespice> /settings.d` folder are automatically integrated in alphabetical order and are therefore prefixed with numbers.

If you want to add additional configurations yourself, you can save your own files here. For this, it is recommended to use the prefix 001-.

Additional configurations, which are not packed per default but can be used, can be found at [auf github.com](https://github.com).