


Manual:Extension/BlueSpicePermissionManager/Cloud

A [quality version](#) of this page, [approved](#) on *21 April 2021*, was based off this revision.


To manage permissions, you use the Permission manager. It is located under *Global actions > Management > Permission manager*. This links to the page `Special:PermissionManager`.

Permission types


An administrator can select between three permission settings. By default, the wiki is set to be **private**.


**Protected wiki**

- Everyone can **view** the content - including anonymous users
- Only logged-in users can **edit** the content
- Only users in the group "sysop" can perform **administrative actions**


**Private wiki**

- Only logged-in users can **view and edit** the content
- Only users in the group "sysop" can perform **administrative actions**



**Custom setup**

- Assign roles and groups manually



Permission manager settings

Permission type	Description
Protected wiki	The wiki is visible to anyone. Only logged-in users can edit the wiki. <ul style="list-style-type: none">All users have edit rights by default.To approve a page (if the approval mechanism is activated in a namespace), the groups "editor" and "reviewer" must be assigned to a user.To manage the wiki (administrative tasks), the group "sysop" must be assigned to a user.
Private wiki	Only logged-in users can view and edit the wiki. <ul style="list-style-type: none">To edit a page, users must be assigned to the "editor" group.To approve a page (if the approval mechanism is activated in a namespace), the groups "editor" and "reviewer" must be assigned to a user.To manage the wiki (administrative tasks), the group "sysop" must be assigned to a user
Custom	Roles and groups are assigned by an administrator. This is necessary if different

Permission type	Description
setup	namespaces need to have different user rights.

Note: In BlueSpice pro Cloud, it is not possible to assign *edit*, *comment*, or *upload* rights to anonymous users.

Custom setup

Important! If you want to manually manage the permissions in your wiki, you need to be familiar with the concept of groups and roles in the wiki. Please check the necessary info about the [BlueSpice Permission manager](#) before assigning roles to groups.

The following table lists a typical basic custom setup (you do not need to change any settings for other listed default groups):

User group	Initially assigned roles	Purpose of this group	Suggested role
anonymous users (*)	reader	Group members can read wiki content.	(no role assignment) or <i>reader</i>
user	reader, editor	Determines the rights authenticated users have if they don't belong to any other groups. All groups besides anonymous users initially inherit permissions from this group.	<i>reader</i> or <i>reader, editor</i>
bureaucrat	(inherited from user). accountmanager	Group members can add user groups and assign groups to users without needing full sysop permissions.	<i>accountmanager</i>
editor	(inherited from user)	Group members can edit the wiki.	<i>editor</i>
interface-admin	(inherited from user)	Group members can execute maintance tasks such as style changes or global text replacements, but do not have permissions related to other sysop tasks, such as user or namespace management.	<i>structuremanager</i>
	(inherited from user),		

User group	Initially assigned roles	Purpose of this group	Suggested role
reviewer	reviewer	Group members can approve page revisions if the approval feature is activated.	<i>reviewer</i>
sysop	(inherited from user), admin	Grants administrator rights to the wiki. Included in roles: admin, maintenanceadmin	<i>admin</i>