

Reference:ContentTransfer

Extension\ ContentTransfer

Overview			
Description:	Copies new or existing wiki pages into a different wiki. (v3.2 and up)		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL v3
Type:	BlueSpice	Category:	Quality Assurance
Edition:	BlueSpice Farm (deactivated)		
View help page			

Features

Users with the appropriate authorization can copy up to 200 pages per transfer from a wiki to the same namespace of a target wiki. This extension usually requires BlueSpice Farm.

Depending on the settings selected on the ContentTransfer special page, the following files are copied:

- the selected wiki pages
- the related category pages
- the book page associated with wiki pages
- the templates associated with wiki pages
- attached files

Technical information

Important! The extension is deactivated by default and must first be activated in 060-ContentTransfer under settings.d - or in the LocalSettings.custom.php in the installation folder (not just in a single farm instance):

```
wfLoadExtension ('ContentTransfer');
```

Configuration

The following information is necessary to transfer content between two wiki instances:

<source-instance-name>

Name of the source wiki. This is the directory name from `/opt/mediawiki/w/_sf_instances/`.

<target-instance-descriptive-name>

Descriptive name of the target wiki. This is usually the same as <target-instance-name>, but can be chosen freely to better describe the instance. Does not allow spaces.

<target-instance-name>

Name of the target wiki. This is the directory name from `/opt/mediawiki/w/_sf_instances/`. It can be extracted from the url of the wiki instance.

<target-instance-label>

The display name for the target wiki. It can contain empty spaces. This information is optional and can be commented out.

<servername>

Server-url

<bot-username-provided>

A user name in the form of `<username>@<id>`.

The bot user has to be generated from

`Special:BotPasswords` in the target wiki.

After you click "Create", a page for selecting the bot rights is shown. Activate the following settings:

- High-volume editing
- Edit existing pages
- Edit protected pages
- Create, edit and move pages,
- Upload new files
- Upload, replace and move files

	Granted
Basic rights ?	<input checked="" type="checkbox"/>
High-volume editing ?	<input checked="" type="checkbox"/>
Edit existing pages ?	<input checked="" type="checkbox"/>
Edit protected pages ?	<input checked="" type="checkbox"/>
Edit your user CSS/JSON/JavaScript ?	<input type="checkbox"/>
Edit your user preferences ?	<input type="checkbox"/>
Edit the MediaWiki namespace and user CSS/JSON/JavaScript ?	<input type="checkbox"/>
Create, edit, and move pages ?	<input checked="" type="checkbox"/>
Upload new files ?	<input checked="" type="checkbox"/>
Upload, replace, and move files ?	<input checked="" type="checkbox"/>
Patrol changes to pages ?	<input type="checkbox"/>
Rollback changes to pages ?	<input type="checkbox"/>
Block and unblock users ?	<input type="checkbox"/>
Bot user settings	

<bot-password-provided>

The password is created in the wiki and needs to be used in the settings below.

With all this info, open `/opt/mediawiki/w/_sf_instances/<source-instance-name>/LocalSettings.custom.php`.

Add the following info:

```
$wgContentTransferTargets['<target-instance-descriptive-name>'] = [
    "url" => "https://<servername>/<target-instance-name>/api.php",
    "user" => "<bot-username-provided>",
    "password" => "<bot-password-provided>",
    "draftNamespace" => "Draft",
    "pushToDraft" => true,
    "displayText" => "<target-instance-label>",
];
```

If ContentTransfer is used without the extension [MergeArticles](#), the information about drafts has to be deactivated in the settings block:

```
# "draftNamespace" => "Draft",
"pushToDraft" => false,
```

Example:

```
$wgContentTransferTargets['MeinWiki'] = [
    "url" => "http://172.16.200.23/MeinWikiName/api.php",
    "user" => "Snow@Schneewittchen",
    "password" => "uuicqdv9mubfrepbpqu1bvsl5957cpa9",
    # "draftNamespace" => "Draft",
    "pushToDraft" => false,
    "displayText" => "Mein Wiki",
];
```

Note: To conclude the configuration, you need to run `update.php`

Additional settings\:

```
$wgContentTransferIgnoreInsecureSSL = false; // Ignore invalid SSL certificates (for
test systems)
$wgContentTransferPageLimit = 200; // Max number of pages to be allowed at one
$wgContentTransferOnlyContentNamespaces = true; // Only allow content namespaces to be
selected in filters
$wgContentTransferAllowTalkNamespaces = false; // Allow talk namespaces to be selected
in filters
```

Anforderungen

ContentTransfer requires [BlueSpiceFoundation](#). Pages that already exist in the target wiki, can be merged using the extension [MergeArticles](#).