

Setup:Installation Guide/System Preparation/Windows/Parsoid

A [quality version](#) of this page, [approved](#) on *4 November 2021*, was based off this revision.

Contents

1 Installing Parsoid	2
2 Creating the configuration file	3
3 Parsoid installation and configuration check	3
4 Installation as a service	4
5 Next step	7



Parsoid is the rendering service for the Visual Editor. The steps listed here are optional and only required if you want to use Visual Editor in your BlueSpice installation. After your BlueSpice Installation, you still have to [activate VisualEditor](#).




For the installation and operation of Parsoid, [Git](#) and [Node.js](#) are required. If you have not installed them yet, follow the links that are provided here.

Installing Parsoid

Important! Please make sure to use the correct version of Parsoid during installation. The currently supported version is Parsoid 0.10.0.

1. First, open the Windows Command Prompt as administrator. To do this, right-click "Start" (1) and select "Command Prompt (Administrator)" (2):



2. Change into the directory `C:\bluespice\bin\npm\node_modules` and execute the command:

```
npm install --global parsoid
```

3. Change into the parsoid directory C:\bluespice\bin\npm\node_modules\parsoid:

```
cd parsoid
```

4. Execute the command:

```
npm install
```


Keep the command prompt open and complete the next steps.

Creating the configuration file

In the BlueSpice codebase you will find two files in the folder `extensions/BlueSpiceVisualEditorConnector/docs/parsoid`:

- `config.yaml`
- `localsettings.js`

Copy them into the folder C:\bluespice\bin\npm\node_modules\parsoid\.




This provides an already finished configuration of Parsoid, which should work in the standard setup without further adjustments.

Parsoid installation and configuration check

To test the installation and configuration, go back to the command prompt.


Change into the directory `C:\bluespice\bin\npm\node_modules\parsoid` (1) and start the service with the command `"node bin\server.js"` (2):



```
Administrator: Command Prompt - node bin\server.js
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Windows\system32>cd \bluespice\bin\npm\node_modules\parsoid
C:\bluespice\bin\npm\node_modules\parsoid>node bin\server.js
{"name":"parsoid","hostname":"WIN-038Q5BR850L","pid":4044,"level":30,"levelPath":"info/service-runner","msg":"master(4044) initializing 2 workers","time":"2018-11-15T19:00:57.836Z","v":0}
{"name":"lib/index.js","hostname":"WIN-038Q5BR850L","pid":4516,"level":30,"levelPath":"info","msg":"loading ...","time":"2018-11-15T19:01:01.098Z","v":0}
{"name":"lib/index.js","hostname":"WIN-038Q5BR850L","pid":4516,"level":30,"levelPath":"info","msg":"ready on :8000","time":"2018-11-15T19:01:01.234Z","v":0}
{"name":"lib/index.js","hostname":"WIN-038Q5BR850L","pid":520,"level":30,"levelPath":"info","msg":"loading ...","time":"2018-11-15T19:01:03.673Z","v":0}
{"name":"lib/index.js","hostname":"WIN-038Q5BR850L","pid":520,"level":30,"levelPath":"info","msg":"ready on :8000","time":"2018-11-15T19:01:03.767Z","v":0}
{"name":"parsoid","hostname":"WIN-038Q5BR850L","pid":4044,"level":40,"levelPath":"warn/service-runner","msg":"Startup finished","time":"2018-11-15T19:01:03.806Z","v":0}
```

The service should now start without an error message. For further review, call the URL "<http://localhost:8000>" in Internet Explorer. You should see the following page:



Change back to the command prompt and quit Parsoid by pressing `"Ctrl+C"`. Keep the command prompt open and go to the next step.

Installation as a service

To run Parsoid in the background in the future, you need to install Parsoid in a Windows service. To do this, proceed as follows:

In the command prompt, change to the directory `"C:\bluespice\bin\npm"` (1) and execute the command `"npm install node-windows"` (2):

```

4) initializing 2 workers", "time": "2018-11-15T19:00:57.836Z", "v": 0}
{"name": "lib/index.js", "hostname": "WIN-038Q5BR850L", "pid": 4516, "level": 30, "levelPath": "info", "msg": "loading ...", "time": "2018-11-15T19:01:01.092Z", "v": 0}
{"name": "lib/index.js", "hostname": "WIN-038Q5BR850L", "pid": 4516, "level": 30, "levelPath": "info", "msg": "ready on :8000", "time": "2018-11-15T19:01:01.234Z", "v": 0}
{"name": "lib/index.js", "hostname": "WIN-038Q5BR850L", "pid": 520, "level": 30, "levelPath": "info", "msg": "loading ...", "time": "2018-11-15T19:01:03.673Z", "v": 0}
{"name": "lib/index.js", "hostname": "WIN-038Q5BR850L", "pid": 520, "level": 30, "levelPath": "info", "msg": "ready on :8000", "time": "2018-11-15T19:01:03.767Z", "v": 0}
{"name": "parsoid", "hostname": "WIN-038Q5BR850L", "pid": 4044, "level": 40, "levelPath": "warn/service-runner", "msg": "Startup finished", "time": "2018-11-15T19:01:03.866Z", "v": 0}
{"name": "parsoid", "hostname": "WIN-038Q5BR850L", "pid": 4044, "level": 30, "levelPath": "info/service-runner/master", "msg": "master shutting down, killing workers", "time": "2018-11-15T19:07:38.800Z", "v": 0}
{"name": "parsoid", "hostname": "WIN-038Q5BR850L", "pid": 4044, "level": 30, "levelPath": "info/service-runner/master", "msg": "Exiting master", "time": "2018-11-15T19:07:38.818Z", "v": 0}

C:\bluespice\bin\npm\node_modules\parsoid>cd C:\bluespice\bin\npm
C:\bluespice\bin\npm>npm install node-windows
npm WARN saveError ENOENT: no such file or directory, open 'C:\bluespice\bin\npm\package.json'
npm WARN enoent ENOENT: no such file or directory, open 'C:\bluespice\bin\npm\package.json'
npm WARN npm No description
npm WARN npm No repository field.
npm WARN npm No README data
npm WARN npm No license field.

+ node-windows@0.1.14
added 3 packages from 8 contributors in 9.488s

C:\bluespice\bin\npm>

```

Using a text editor, create the file "C:\bluespice\bin\npm\node_modules\parsoid\ parsoid.service" with the help of [this linked content](#):

```

var Service = require('node-windows').Service;

// Create a new service object
var svc = new Service({
  name: 'Parsoid Web Service',
  description: 'Parsoid Web Service for MediaWiki',
  script: 'C:\\bluespice\\bin\\npm\\node_modules\\parsoid\\bin\\server.js'
});

// Listen for the "install" event, which indicates the
// process is available as a service.
svc.on('install', function() {
  svc.start();
});

svc.install();

```

In the command prompt, change into the directory "C:\bluespice\bin\npm\node_modules\ parsoid" (1) and execute the command "node parsoid.service" (2):

```

0: "2018-11-15T19:01:01.234Z", "v": 0}
{"name": "lib/index.js", "hostname": "WIN-038Q5BR850L", "pid": 520, "level": 30, "levelPath": "info", "msg": "loading ...", "time": "2018-11-15T19:01:03.673Z", "v": 0}
{"name": "lib/index.js", "hostname": "WIN-038Q5BR850L", "pid": 520, "level": 30, "levelPath": "info", "msg": "ready on :8000", "time": "2018-11-15T19:01:03.767Z", "v": 0}
{"name": "parsoid", "hostname": "WIN-038Q5BR850L", "pid": 4044, "level": 40, "levelPath": "warn/service-runner", "msg": "Startup finished", "time": "2018-11-15T19:01:03.866Z", "v": 0}
{"name": "parsoid", "hostname": "WIN-038Q5BR850L", "pid": 4044, "level": 30, "levelPath": "info/service-runner/master", "msg": "master shutting down, killing workers", "time": "2018-11-15T19:07:38.800Z", "v": 0}
{"name": "parsoid", "hostname": "WIN-038Q5BR850L", "pid": 4044, "level": 30, "levelPath": "info/service-runner/master", "msg": "Exiting master", "time": "2018-11-15T19:07:38.818Z", "v": 0}

C:\bluespice\bin\npm\node_modules\parsoid>cd C:\bluespice\bin\npm
C:\bluespice\bin\npm>npm install node-windows
npm WARN saveError ENOENT: no such file or directory, open 'C:\bluespice\bin\npm\package.json'
npm WARN enoent ENOENT: no such file or directory, open 'C:\bluespice\bin\npm\package.json'
npm WARN npm No description
npm WARN npm No repository field.
npm WARN npm No README data
npm WARN npm No license field.

+ node-windows@0.1.14
added 3 packages from 8 contributors in 9.488s


C:\bluespice\bin\npm>cd C:\bluespice\bin\npm\node_modules\parsoid
C:\bluespice\bin\npm\node_modules\parsoid>node parsoid.service
C:\bluespice\bin\npm\node_modules\parsoid>

```


You can now close the command prompt.

Then enter the key combination Windows+R.


In the following dialog box, enter "services.msc" (1) and confirm with "OK" (2):



Find the service "Parsoid Web Service" and open it with a double-click:



Select the startup type "Automatic" (1) and start the service (2). After the service is started, close the window with "OK" (3):



In Internet Explorer, check the URL "<http://localhost:8000>", as already explained in the previous step, whether the Parsoid service started successfully.

Next step

If you have completed all steps successfully, you can proceed to the next step "[Python](#)".