

Setup:Installation Guide/Webservices/PDF-Export

A quality version of this page, approved on 17 October 2018, was based off this revision.

Contents	
1 Tips for this Document	2
2 Copying the BShtml2PDF Application	2
3 Restart Tomcat	2
4 Activating the PDF Export in BlueSpice	2
5 Troubleshooting	3



This document describes the installation of BlueSpice - PDF export. Please make sure that the Apache Tomcat server is completely installed and configured at the BlueSpice server.

Tips for this Document

- Please, read this manual completely and work through the single installation steps one after another.
- For editing the configuration files with a text editor, the files must be saved in UTF-8 coding without BOM (Byte Order Mark).
- The placeholder <installpath-bluespice> stands for the path to your BlueSpice installation, e.g C: \inetpub\wwwroot\bluespice (Windows) or /var/www/bluespice (Linux).
- The placeholder <tomcat-webapps> stands for the path to the Webapps directory of your Tomcat server, e.g. C:\Program Files\Apache Software Foundation\Tomcat 8.5\webapps (Windows) or /var/lib/tomcat8/webapps (Linux).

Copying the BShtml2PDF Application

Move the file "BShtml2PDF.war" from the directory <installpath-bluespice>/extensions/BlueSpiceExtensions/UEModulePDF/webservices to <tomcat-webapps>

Restart Tomcat

Restart the Tomcat Webserver like described here.

Activating the PDF Export in BlueSpice

Go to the directory <installpath-bluespice>/settings.d . Open the file **020-BlueSpiceUEModulePDF.php** in a text editor.

In the second line is a code to activate the extension:

```
return; // Disabled. Needs Tomcat
```

You can either add a comment character (#) to the beginning of this line or delete the line completely, save the file and exit it.

Open a command line and change to the <installpath-bluespice> folder. Execute the following command:

```
php maintenance/update.php (Linux)
php maintenance\update.php (Windows))
```



In Windows, make sure that the environment variables are set correctly to access the php command.





Note that you must update the file system permissions after running update. php.

When the script is finished with the "Done" message, the web service is successfully installed.

```
Modifying event_extra field of table echo_event ...done.
Modifying event_agent_ip field of table echo_event ...done.
...have etp_id field in echo_target_page table.
...have notification bundle base field in echo_notification table.
...echo_event table does not contain event_timestamp field.
...have eeb_event_hash field in echo_ewent table.
...have event_page_id field in echo_event_table.
...table_exho_event_time_already_set_on_exho_event_table.
   ..index echo_event_type already set on echo_event table.
..index echo_user_timestamp already set on echo_notification table.
  Creating titlekey table...ok. Rebuilding titlekey table...
... l ok.
... l ok.
...hitcounter table does not exist, skipping modify field patch.
Creating htt_counter_extension table ...done.
Creating htt_counter table ...done.
...page table does not contain page_counter field.
Creating bs_editnotifyconnector table ...done.
Creating bs_namespacemanager_backup_page table ...done.
Creating bs_namespacemanager_backup_revision table ...done.
Creating bs_namespacemanager_backup_text table ...done.
Adding page_content_model field to table bs_namespacemanager_backup_page ...done.
Adding rev_shai field to table bs_namespacemanager_backup_revision ...done.
Adding rev_content_model field to table bs_namespacemanager_backup_revision ...done.
Creating bs_permission_templates table ...done.
Creating bs_usagetracker table ...done.
Creating bs_usagetracker table ...done.
Creating bs_pagetemplate table ...done.
    .. 1 ok.
   ..se text field does not exist in bs_saferedit tal
treating bs_readers table ...done.
..have readers ts field in bs_readers table.
..site_stats is populated...done.
thecking existence of old default messages...done.
   opulating rev_len column
..doing rev_id from 1 to 200
 Populating ar_len column

...archive table seems to be empty.

rev_len and ar_len population complete [0 revision rows, 0 archive rows].

Populating rev_shal column
   ..doing rev_id from 1 to 200
copulating ar_sha1 column
..archive table seems to be empty.
 rev shal and ar shal population complete [0 revision rows, 0 archive rows].
Done 0 files in 0.0 seconds
Fixing protocol-relative entries in the externallinks table...
 Done, 0 rows updated.
Populating fa_sha1 field from fa_storage_key
Updating *_from_namespace fields in links tables.
...doing page id from 1 to 200
Purging caches...done.
   one in 1.6 s.
coot@bluespice:/var/www/bluespice#
```

Troubleshooting

If there is a problem with PDF export in BlueSpice, first check the file system permissions.