

Contents

1.	. Logo	2
2	. Manual:Extension/BlueSpiceConfigManager	.2
3	. Manual:Extension/FlexiSkin	9
4	. Reference:FlexiSkin	0



Logo

FlexiSkin allows you to customize the look and feel of your wiki. You can change the design of your wiki via a Special page and with a preview function. Easily insert your own logo and favicon and define the colors and font settings you want to achieve a custom look.

Important! FlexiSkin is only available in BlueSpice pro Cloud. To upload the logo in BlueSpice 3, follow the instructions for the Config Manager.

Contents



Where to find FlexiSkin?

The FlexiSkin settings can be adjusted on the page *Special:FlexiSkin* (- watch the spelling as the wiki is case-sensitive).


Logo and Favicon

Logo


The fastest way to customize your wiki is to simply upload your own logo.

To upload your logo:

1. **Click** *Select a file* to choose a file from your file explorer **or drag the file** into the dotted area of the Logo upload area.



2. **Click** Preview to see the positioning of your logo.



3. **Check** the logo preview in your wiki.






4. To **upload a different logo**, click the x-icon in the logo upload area and repeat the previous steps.



5. **Save and activate** the logo or continue with theming your wiki.



6. **Click** *OK* to acknowledge that the changes are applied immediately and affect all wiki users.

Tips for working with the logo

By default, the logo is placed at the left side of the top bar with a left-padding of applied. To remove the left padding, you can add the following css declaration to the *Free CSS* area in Flexiskin:




Note: You first have to save the page to view the logo changes made in Free Css. The preview does not reflect these changes.

Favicon

You can also upload your own favicon. The favicon is the image that is shown in the browser tabs. Follow the steps for uploading a logo, just use the favicon upload area instead.



After saving the page, you will see your custom image in the browser tabs of your wiki pages.




Theming

Color presets

The fastest way to customize your wiki colors is to pick a color preset from the available themes. You can fine-tune each theme as needed if one or another color requires tweaking.



The available standard themes are shown here.




Custom color scheme

Starting with a custom color scheme, you can further adjust individual skin colors to match your own color scheme.

To get started, click on the edit icon next to a color scheme. In my example, I want to have text and a neutral background in my navigation, so I pick "sunflower dark" and then edit it. But first, let's look at the color assignments.





Background color	Foreground (=text) color	User interface elements	
Color 1	Color 1	left navigation, edit and create buttons with drop down menus, user profile menu	
Color 2	Color 2	page tools / quality management tools	
Color 3	Color 3	top bar (since there is no text in the top bar, the foreground color only sets the color of the toggle icons)	
Color 4	Color 4	custom menuwith drop down menus	
Body background	-	Page background. It is mainly visible when the navigation pane and the tools pane are minimized.	






As an example, we make some color changes.




This results in the following color scheme:





Content

In the content settings, you can adjust styles related to the actual content area (2) of the wiki page:






Note: You first have to save the page to view the changes made to the content settings. The preview does not reflect these changes.

Colors

Background color	Foreground (=text) color	User interface elements
Content background		Page background. It is mainly visible when the navigation pane and the tools pane are minimized.
	Content color	Color of the flowtext of the wiki page.
	Valid link	Link color that indicates that a linked page exists (standard link).
	Broken link	Link color that indicates that the linked page doesn't exist ("redlink") .
Content background	Header 1-6	Color for the individual heading levels. (1) Header 1: Page title (2) Header 2: Heading, ToC heading (3) Header 3: Sub-heading 1 (4) Header 4: Sub-heading 2 (5) Header 5: Sub-heading 3 (6) Header 6: Sub-heading 4 (7) FirstHeading: Automatically generated page title in the title section (color only adjustable via Free CSS)
	Color 4	custom menuwith drop down menus





Font

You can also change the font settings for the wiki pages. These settings only apply to the text in the content area. The text in other areas, such as the navigation and the tools panels or the top menus, is not affected.

Layout

You can also change the width of the content area, if you want to. Just make sure to test it on many devices to make sure that it works as intended, since wiki users work with different display settings. Unless you have a specific reason to change the content width, there is no need to make adjustments to this setting.

Headings

For all heading levels, you can adjust color, font size and underlining of the different heading levels. You can also change the unit type for your font-settings (e.g, px instead of rem). If you are not familiar with the differences between the unit types, simply leave the default setting of *rem*.



Free CSS

For additional adjustments that are not possible with the FlexiSkin settings, you can use the *Free CSS* field if you are familiar with CSS. We already looked at how you can adjust your logo position with CSS.

Note: You first have to save the page to view the logo changes made in Free Css. The preview does not reflect these changes.

Example1: Change the color of the page title

To change the color of the automatically generated page title in the title area, add this code to the *Free CSS* field:

```
/* color for automatically generated page title in the title section*/
#content #firstHeading {
   color: #3f51b5;
}
```

Related info

Reference:FlexiSkin

Config manager

A quality version of this page, approved on 6 October 2021, was based off this revision.

Contents

```
      1 Layout
      14

      1.1 Filter options
      14

      1.2 Searching for settings
      14

      2 Settings by extension
      15

      2.1 BlueSpiceFoundation
      15

      2.1.1 Updating logo and favicon
      15

      2.1.2 System
      16

      2.2 BlueSpiceAbout
      16

      2.3 BlueSpiceArticleInfo
      17

      2.4 BlueSpiceAuthors
      17

      2.5 BlueSpiceAvatars
      18
```

2.6 BlueSpiceBookshelf	18	}
2.7 BlueSpiceChecklist	. 20	0
2.8 BlueSpiceExtendedSearch	. 20	0
2.9 BlueSpiceExtendedStatistics	. 2:	1
2.10 BlueSpiceInsertCategory	. 2:	1
2.11 BlueSpicensertLink	. 2:	1
2.12 BlueSpicePageTemplates	. 22	2
2.13 BlueSpicePermissionManager	. 22	2
2.14 BlueSpiceRSSFeeder	. 22	2
2.15 BlueSpiceReaders	. 22	2
2.16 BlueSpiceSaferEdit	. 23	3
2.17 BlueSpiceUEModuleBookPDF	. 23	3
2.18 BlueSpiceUEModuleHTML	. 24	4
2.19 BlueSpiceUEModulePDF	. 24	4
2.20 BlueSpiceUniversalExport	. 25	5
2.21 BlueSpiceVisualEditorConnector	. 25	5
2.22 BlueSpiceWholsOnline	. 25	5
2.23 BlueSpiceExpiry	. 25	5
2.24 BlueSpiceReview	. 26	ô
2.25 BlueSpiceReviewExtended	. 26	ô
2.26 BlueSpiceFlaggedRevsConnector	. 26	ô
2.27 BlueSpiceSocialBlog	. 27	7
2.28 BlueSpiceSocialTopics	. 28	8
2.29 BlueSpiceMatomoConnector	. 29	9
3 Related info	. 29	9




With the Config manager, a wiki user with *sysop* rights can manage BlueSpice wiki-wide settings in one place. In the <u>navigation</u>, it is located under *Global navigations > Management > Config manager*. This link loads the page *Special:ConfigManager*.

Layout

Filter options

All settings can be accessed through the following filter options:

- **Feature:** group by type of functionality the setting belongs to (search, administration...)
- **Extension:** group by extension name
- **Package:** group by BlueSpice edition and services (BlueSpice free, BlueSpice pro, Matomo)



All settings are available in any type of grouping. Changing the grouping type does not add or remove setting options. It just groups them differently. After settings are adjusted, they can be saved by clicking *Save*, or cancelled by clicking *Reset*.


Note: If a server administrator has configured a setting to no longer be writable, it will be shown as greyed-out in the config manager. You will have to talk to your server administrator about changing such a setting.

Searching for settings

A search bar is located above the list of settings. Type in a keyword such as "logo" to find the corresponding setting. The search returns settings regardless of the currently selected group.

Note: The search field has to be empty if you want to see the filter menu instead of the search.





Settings by extension


BlueSpiceFoundation

Updating logo and favicon

• **Logo path:** The logo image should be stored in the /images folder of your installation. If you store it in the /skins folder of your BlueSpice installation, it could be overwritten with an upgrade.


To upload the logo directly in the wiki:

- 1. **Upload** the logo on the page *Extended file list* (*Special:ExtendedFilelist*). This is a link under the *Global actions* navigation.
- 2. **Search** for the logo name in the extended file list.
- 3. Click on the thumbnail image of the logo. This opens the logo on a separate page.




4. **Copy** the relative logo path from the address bar.In a typical Wiki configuration, this path starts with /w/.....





5. **Paste** the logo path into the text field for the logo.



- 6. Click Save.
- 7. **Refresh** the page (Strg+F5).

If the uploaded logo is too large, you can add the following code snippet to the page *MediaWiki:Common. css.* This automatically adjusts the image to the height of the main toolbar:

```
.bs-logo a {background-size: contain;}
```

• **Favicon path:** The favicon image should be stored in the */images* folder of your installation. If you store it in the /skins folder of your BlueSpice installation, it could be overwritten with an upgrade. Favicon images have the file extension .ico.

System


- Allowed file extensions: For security reasons, the types of files that users can upload are restricted. Here, you can allow additional file formats. If a file format is blacklisted in the server configuration, adding this file extension here will not allow this file type to be uploaded. See mediawiki.org/wiki/Manual: Page title for more info.
- Allowed image extensions: The standard web image types are listed here. In general, you want to restrict image uploads to web images. See developer.mozilla.org/en-US/docs/Web/Media/Formats /Image_types for more on browser-supported image types.

BlueSpiceAbout

• Show link "About BlueSpice" in the main menu: Shows or hides the link to the page AboutBlueSpice in the main navigation.








BlueSpiceArticleInfo

BlueSpiceArticleInfo, together with BlueSpiceAuthors, BlueSpiceReaders, and BlueSpiceExtendedSearch is part of the Page information in the quality management tools.


• **Update interval in seconds:** Sets the refresh rate for the "Last edit" value. By default, this date is updated every 10 seconds via JavaScript.




BlueSpiceAuthors

BlueSpiceAuthors, together with *BlueSpiceArticleInfo* and *BlueSpiceReaders*, is part of the *Page information* in the quality management tools.

Display authors: Show or hide authors on the page information page.








BlueSpiceAvatars

An avatar image is automatically generated if the user does not upload a profile picture or if the user decides to create an avatar image in the preferences.

Generator

- InstantAvatar: Generates an avatar image based on using the initials of the Real name or the Username
- Identicon: Generates an avatar image based on parts of the user's IP address.







BlueSpiceBookshelf

- Show book chapter pager after content: Displays previous/next book page navigation at the end of each book page. (1)
- Show book chapter pager before content: Displays previous/next book page navigation at the beginning of each book page. (2)





• Use the display title from book source on article: Shows the title from the book navigation as page title instead of the page name.



Note: If the page additionally contains a {{DISPLAYTITLE}} tag, the display title of the page is shown instead of the book title.

- Prepend article table of contents and headlines with book numberation
- Supress namespace prefix of book articles in output



BlueSpiceChecklist

Mark checklist changes as minor edit: If this setting is active, changes to a checklist (for example, checking a checkbox) in view mode are logged as minor edits. If this setting is inactive, a change to the checklist is recorded as a regular version in the page history.

```
• (cur | prev) © 12:01, 2019 December 5 ML Mlink-rodrigue (talk | contribs | block m.)
(2,820 bytes) (+9) . . (Unchecked checkbox #1) (rollback 6 edits | undo) (Tag: Checklist change)
minor edit
```

BlueSpiceExtendedSearch


- **External file paths**: External locations to scan for and index files from. These locations are entered in key/value pairs of Physical path and URL prefix.
 - O Physical path: Storage path. For mounted drives, for example: X:|Documents
 - URL prefix: All files indexed from the indexed physical location are prefixed in the search results. It should be used if files are available from a web server. By default, the URL prefix is set to the same value as Physical path.

Examples for external file paths

Example file	Phys. Path	URL Prefix	Link in results list
	S:\	file:///S:/	file:///S:/Sales/Info/glossary.pdf
		https://sharepoint	https://sharepoint/Sales/
		/Sales/ documents/	documents/Sales/Info/glossary.
S:\Sales\Info\glossaryy.pdf		documents/	pdf
		https://intranet /showdocs	https://intranet/showdocsinline. aspx?
		/Silowdoes	uspx.
		inline.aspx?path=	path=/Sales/Info/glossary.pdf
/var/www/bluespice/w /mounted_	/var/www/bluespice		https://wiki.company.local/w
shara/Calas/Infa/alassary	/w/		/mounted_
share/Sales/Info/glossary. pdf	mounted_share/		share/Sales/Info/glossary.pdf

•	Use simple auto	complete: forces a	more compact au	tocomplete (1-col	lumn Sales thumbna	il preview).





- **Automatically set language filter**: This setting applies to multi-languageSalesIt returns seyarch results for a user only in the user's language. Users can set their language in their preferences.
- **Exclude patterns:** Files at external file locations can be exluded from search based on regular expression patterns.

BlueSpiceExtendedStatistics

- Exclude these users: Some user groups, like WikiSysop can skew the statistics, for example the statistics for search queries or because they complete automated maintenance tasks. These types of user groups can be excluded from the statistical results.
- Maximum number of interval steps: Sets the size of the x-axis for the results. For a few days, select
 the interval Day or Calendar Week, for periods over one year, select Year or Month. If you do not get any
 results for your query, try to adjust the interval accordingly.

BlueSpiceInsertCategory

- Insert category with its parents
- Set page categories as default in upload dialog

BlueSpicensertLink

Allow unmapped links



- Allowed locations for external files
 - Filesystem prefix
 - O Web accessible prefix:

BlueSpicePageTemplates


- Force target namespace:
- **Hide default templates:** Hides the default *Empty page* template.

BlueSpicePermissionManager

Backup limit: Sets the number of backups for the permissions manager. Each time the page Special:
 PermissionManager is saved, a backup is created. If the backup limit is set to 5, the last five versions of the permissions configuration are saved as backups.

BlueSpiceRSSFeeder


- **URL whitelist:** RSS feeds need to be whitelisted here by an administrator before they can be displayed in a wiki page.
- Maximum number of allowed redirects: If there are URL redirects for any of the whitelisted URLs, the number of redirects needs to be adjusted (usually to 1 or 2).



BlueSpiceReaders

 Number of readers to display: Sets the number of readers that are displayed on the Page information in the Quality management tools.






BlueSpiceSaferEdit

- **Interval for lookup for concurrent editings:** Sets the time in seconds for checking if another person is editing the page.
- Show name of current editor: Shows or hides the name of the user who is currently editing the page.

BlueSpiceUEModuleBookPDF

- Table of Contents
 - Only article titles (indent by grade): Only shows the article titles in the main contents table of the PDF.



• Embed article TOCs (No indent of article titles): Shows the table of contents for each article in the main contents table of the PDF.



	Table of contents
1	Introduction5
2	Wiki pages model
	1 The pages modell6
	2 Page types6
	2.1 Special page
	2.2 Content page
	2.3 Wiki page
	2.4 Category page
	2.5 File / image (description) page
3	User rights
3	3.1 Group manager
	1 Accessing the group manager
	2 Functionality
	3 Assigning roles and users to groups18

BlueSpiceUEModuleHTML

• Hide namespace prefix in PDF: If activated, the namespace is shown in the HTML main heading.

Note: If the page contains a "displaytitle" tag in the page source, the page display title is shown and this setting has no effect.

BlueSpiceUEModulePDF

• **Hide namespace prefix in PDF:** If activated, the namespace is shown in the PDF main heading for a page.



Note: If the page contains a "displaytitle" tag in the page source, the page display title is shown and this setting has no effect.



BlueSpiceUniversalExport

- **Metadata (standard, JSON):** Additional data to be passed to the rendering template in JSON format. This data can be used in the export template. The template itself is maintened server-side.
- Metadata (override, JSON): Allows overriding standard data sent to the rendering template in JSON format. Values that are set by default can be overriden with this option.

BlueSpiceVisualEditorConnector


- Enable VisualEditor for BlueSpice extensions
- Configuration variable to use a simplified save process
- Upload type
 - Original (Here a confirmation of the rights of use/upload is obtained, file name and namespace of the file can be changed, a category can be assigned and a description of the file MUST be given).
 - Simple (No confirmation of required rights is obtained here, the name and namespace of the file can be changed, a description and a category can be assigned, but does not have to be specified)
 - One click (No confirmation about required rights is obtained here, the image cannot be renamed and no category can be assigned. Only the namespace can, but does not have to be adjusted before uploading)

BlueSpiceWholsOnline

- Time in seconds until a user is marked as offline: The system checks every x seconds if a user logged out and no longer displayed as online. This can be less frequent than the update inteval for newly logged-in users.
- **Update interval in seconds:** The system checks every *x* seconds for users.

BlueSpiceExpiry

- Show watermark for expired pages in PDF: Shows the watermark for expired pages in PDFs.
- Show watermark for expired pages in print version: Shows the watermark for expired pages when a page is printed.
- Show watermark for expired pages: Shows a watermark on the page itself.





BlueSpiceReview

Only the owner of a review can change it: If this is unchecked, any user with edit rights can update
a workflow.

BlueSpiceReviewExtended

 Workflow will be added to page history: This enables that workflow votes are listed under the page history with the corresponding version.




BlueSpiceFlaggedRevsConnector

Export

The export settings affect how the pages of a book are generated in the PDF export.

Bookshelf: List accepted revisions log: Shows a log of stable page versions of pages in the PDF and
when these pages were put into accepted status. If editors did not provide a comment when accepting
the page, the Stable comment field for a revision is empty.




 Bookshelf: List pages without stable revision: Displays a list of PDF pages at the beginning of the PDF that only exist as a first draft and have no released version.






 Bookshelf: List pages without FlaggedRevs: Displays a list of PDF pages that do not have a release mechanism at the beginning of the PDF.



• **UEModulePDF: Show FlaggedRevs info below main heading**: Prints the latest revision dates (last acceptance and last edit date) below the heading.



Quality assurance

- Automatically set the page to stable, when the workflow was finished successfully: The workflow ends with setting the page status to stable. (this setting is available until version 3.1)
- Automatically delete the workflow, when a page was marked as stable: The workflow is deleted.
- Show unstable pages for following groups: If the group *user* is removed from the *BlueSpiceFlaggedRevs* configuration, users in this group will not be able to see draft versions when they are added as reviewers in a review process. When the group user is removed, only *sysop* and *reviewer* users can access drafts. If you want other groups, for example *editor*, to see draft versions, you need to add them to the configuration. If no user groups are specified in the configuration field, not even reviewers and sysops users will see a visual status indication of a page. They will have access to drafts through the revision history for the page instead.


Searching and Navigation

• **Indexing only stable versions:** Draft versions are excluded from the search results. If a page does not have a stable version, it is not shown as a search result.

BlueSpiceSocialBlog


• **Use teaser text for blog entries in the timeline:** When you create a blog entry, you can create a teaser text for it by clicking the cogwheel symbol in the blog entry form. If this setting is active, the teaser text will be shown on the page *Special:Timeline* instead of the first part of the content.






BlueSpiceSocialTopics

Automatically create all discussion pages. If a user creates the first discussion topic for a page
using the link in the page footer of a wiki page, the needed discussion page is automatically created
first.



A message "This discussion page was created automatically" is inserted on the discussion page.






If this setting is deactivated, the user is directed to the "Create page" default page first

BlueSpiceMatomoConnector

• **Site ID:** Matomo ID of the wiki. You can find the site ID as a url parameter in the browser address bar when you are logged into Matomo.



- Base url: The url to your Matomo installation.
- Show opt-out link in footer: Displays a link in your wiki footer, usually named Analysis service.



On the Analysis service page, there is a checkbox that allows a user to opt-out from being tracked for analysis purposes.

You may choose to prevent this website from aggregating and analyzing the actions you take here. Doing so will protect your privacy, but will also prevent the owner from learning from your actions and creating a better experience for you and other users.

W You are not opted out. Uncheck this box to opt-out.

Matomo opt-out checkbox

Related info

Reference:ConfigManager

FlexiSkin

A quality version of this page, approved on 2 July 2021, was based off this revision.

FlexiSkin allows you to customize the look and feel of your wiki. You can change the design of your wiki via a Special page and with a preview function. Easily insert your own logo and favicon and define the colors and font settings you want to achieve a custom look.



Important! FlexiSkin is only available in BlueSpice pro Cloud. To upload the logo in BlueSpice 3, follow the instructions for the Config Manager.

Contents	
1 Where to find FlexiSkin?	31
2 Logo and Favicon	31
2.1 Logo	31
2.2 Tips for working with the logo	32
2.3 Favicon	33
3 Theming	33
3.1 Color presets	33
3.2 Custom color scheme	34
4 Content	37
4.1 Colors	38
4.2 Font	
4.3 Layout	39
4.4 Headings	39
5 Free CSS	40
5.1 Example1: Change the color of the page title	
6 Related info	40



Where to find FlexiSkin?

The FlexiSkin settings can be adjusted on the page *Special:FlexiSkin* (- watch the spelling as the wiki is case-sensitive).


Logo and Favicon

Logo


The fastest way to customize your wiki is to simply upload your own logo.

To upload your logo:

1. **Click** *Select a file* to choose a file from your file explorer **or drag the file** into the dotted area of the Logo upload area.



2. **Click** Preview to see the positioning of your logo.



3. **Check** the logo preview in your wiki.






4. To **upload a different logo**, click the x-icon in the logo upload area and repeat the previous steps.



5. **Save and activate** the logo or continue with theming your wiki.



6. **Click** *OK* to acknowledge that the changes are applied immediately and affect all wiki users.

Tips for working with the logo

By default, the logo is placed at the left side of the top bar with a left-padding of applied. To remove the left padding, you can add the following css declaration to the *Free CSS* area in Flexiskin:




Note: You first have to save the page to view the logo changes made in Free Css. The preview does not reflect these changes.

Favicon

You can also upload your own favicon. The favicon is the image that is shown in the browser tabs. Follow the steps for uploading a logo, just use the favicon upload area instead.



After saving the page, you will see your custom image in the browser tabs of your wiki pages.




Theming

Color presets

The fastest way to customize your wiki colors is to pick a color preset from the available themes. You can fine-tune each theme as needed if one or another color requires tweaking.



The available standard themes are shown here.




Custom color scheme

Starting with a custom color scheme, you can further adjust individual skin colors to match your own color scheme.

To get started, click on the edit icon next to a color scheme. In my example, I want to have text and a neutral background in my navigation, so I pick "sunflower dark" and then edit it. But first, let's look at the color assignments.





Background color	Foreground (=text) color	User interface elements	
Color 1	Color 1	left navigation, edit and create buttons with drop down menus, user profile menu	
Color 2	Color 2	page tools / quality management tools	
Color 3	Color 3	top bar (since there is no text in the top bar, the foreground color only sets the color of the toggle icons)	
Color 4	Color 4	custom menuwith drop down menus	
Body background	-	Page background. It is mainly visible when the navigation pane and the tools pane are minimized.	






As an example, we make some color changes.




This results in the following color scheme:





Content

In the content settings, you can adjust styles related to the actual content area (2) of the wiki page:






Note: You first have to save the page to view the changes made to the content settings. The preview does not reflect these changes.

Colors

Background color	Foreground (=text) color	User interface elements
Content background		Page background. It is mainly visible when the navigation pane and the tools pane are minimized.
	Content color	Color of the flowtext of the wiki page.
	Valid link	Link color that indicates that a linked page exists (standard link).
	Broken link	Link color that indicates that the linked page doesn't exist ("redlink") .
Content background	Header 1-6	Color for the individual heading levels. (1) Header 1: Page title (2) Header 2: Heading, ToC heading (3) Header 3: Sub-heading 1 (4) Header 4: Sub-heading 2 (5) Header 5: Sub-heading 3 (6) Header 6: Sub-heading 4 (7) FirstHeading: Automatically generated page title in the title section (color only adjustable via Free CSS)
	Color 4	custom menuwith drop down menus





Font

You can also change the font settings for the wiki pages. These settings only apply to the text in the content area. The text in other areas, such as the navigation and the tools panels or the top menus, is not affected.

Layout

You can also change the width of the content area, if you want to. Just make sure to test it on many devices to make sure that it works as intended, since wiki users work with different display settings. Unless you have a specific reason to change the content width, there is no need to make adjustments to this setting.

Headings

For all heading levels, you can adjust color, font size and underlining of the different heading levels. You can also change the unit type for your font-settings (e.g, px instead of rem). If you are not familiar with the differences between the unit types, simply leave the default setting of *rem*.



Free CSS

For additional adjustments that are not possible with the FlexiSkin settings, you can use the *Free CSS* field if you are familiar with CSS. We already looked at how you can adjust your logo position with CSS.

Note: You first have to save the page to view the logo changes made in Free Css. The preview does not reflect these changes.

Example1: Change the color of the page title

To change the color of the automatically generated page title in the title area, add this code to the *Free CSS* field:

```
/* color for automatically generated page title in the title section*/
#content #firstHeading {
   color: #3f51b5;
}
```

Related info

Reference:FlexiSkin

Reference:FlexiSkin

Extension\: FlexiSkin

Overview				
Description:	cription: allows to customize the skin of the wiki.			
State:	stable	Dependency:	MediaWiki	
Developer:	HalloWelt	License:	GPL v2+	
Туре:	MediaWiki	Category:	Skinning	



Overview		
Edition:	BlueSpice Cloud	
	For more info, visit Mediawiki.	

Features

FlexiSkin allows you to customize the skin of your wiki. Choose between different colors or fonts and insert your own logo.

Usage / Features

- dedicated special page Special:Flexiskin
- allows setting of various out of the box themes
- allows definition of custom themes
- fields with color picker
- font type, size and color for headings and content
- logo / favicon upload via drag&drop