

Manual:Extension/BlueSpiceTagSearch

A quality version of this page, approved on 19 May 2021, was based off this revision.

TagSearch allows the integration of a configurable search field in content pages. This search field relies on BlueSpiceExtendedSearch.

Inserting the tag

The tag <bs:tagsearch /> can be inserted and configured directly in visual editing mode.

Go to *Insert > Magic word* in the VisualEditor menu. Select tagsearch from the dialog and click done. This opens the configuration options dialog on the page.

Cancel		TagSearch Ins
Creates a search specified contex	n inp (ts	ut field that searches in
Placeholder	i	Type to search
Туре	í	wikipage X
Namespace(s)	i	Namespace1 Namespace2
Category(-ies)	í	Category1 Category2
Search operator	í	AND

Parameter	Display name	Description
placeholder	Placeholder	Text to be shown in the search field when nothing is typed in
		List of types of search entities to search. By default search entities availble are: <i>wikipage, specialpages, repofile</i> (internal files), <i>externalfile, socialentity</i> . Multiple values can be entered separated by pipe () - "wikipage repofile"

Manual:Extension/BlueSpiceTagSearch



Parameter	Display name	Description	
type	Туре	Note: If a particular namespace is selected, then type "repofile" returns uploaded files that have the associated namespace prefix.	
namespace	Namespace (s)	List of namespaces in which to search. Namespaces can be entered by using their IDs or names, separated by a pipe (). IDs and names cannot be mixed. Correct entries are: "1 6 8", "Help QM", while invalid is "1 QM". To search in the main namespace, use an empty space as value (e.g., " " or " Template")	
category	Category(- ies)	List of categories in which to search. Mutltiple categories must be separated by a pipe () - "Cat1 Cat2"	
operator	Search operator	Applies only to categories. Operator "AND" will only find results that are in all of the given categories, while operator "OR" will show results in any of the given categories.	

Multiple tags can be added to a single page using the same or different configurations.

Using the search field

Once the page is saved, the code for the search field is inserted in the page source where it was inserted.

Example:

```
<bs:tagsearch type="wikipage" operator="AND" namespace=" |Template" category="Editing"
/>
```

The search is looking for wiki pages in the namespaces *(Main)* and *Template* that belong to the category *Editing*.

Clicking on search icon to the left or pressing *Return* loads the full-text search in the Search-Center.

Manual:Extension/BlueSpiceTagSearch



q	Main	8
Ma	in Page	^
Sof	ftware Maintenance and	
Co	nfiguring the trial	
Ter	nplate:Portal Main page.css	
Ð	Create page "Main"	
q	Search full text	~

Related info

• Reference:BlueSpiceTagSearch