

Reference:BlueSpiceSocialTags

Extension\ BlueSpiceSocialTags

Overview			
Description:	Adds tagging functionality to social entities		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-onlyProperty "BSExtensionInfoLicense" (as page type) with input value "</br>GPL-3.0-only" contains invalid characters or is incomplete and therefore can cause unexpected results during a query or annotation process.
Type:	BlueSpice	Category:	Communication
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud		
View help page			

Features

SocialTags provides the option of linked pages to SocialEntities.

Warning: Pages in the namespaces *SocialEntity* and *User* are indexed by search engines by default until prior to version 3.1.13. If you run a public wiki with an earlier version, you should [exclude these namespaces from being searchable](#) unless you want these pages to be indexed by public search engines.

A social entity such as a discussion topic is linked to a wiki page. Users can update these page associations as needed.

The page *Special:SocialTags* shows a filterable list of SocialEntities that share the same tag. The function "watch" is automatically added to all social entities.

Technical Information

This information applies to BlueSpice 3 . Technical details for BlueSpice cloud can differ in some cases.

Requirements

MediaWiki: 1.31
BlueSpiceFoundation: 3.2

- BlueSpiceSocial: 3.2

Integrates into

Special pages

- SocialTags

Permissions

Name	Description	Role
social-tagging	Edit linked pages	admin, author, commenter, editor, maintenanceadmin, reviewer

Configuration

Name	Value
SocialTagsTimelineAfterContentNamespaceBlackList	array ()
SocialTagsTimelineAfterContentShow	false

API Modules

- bs-socialtags-tasks

Hooks

- [BSEntityConfigAttributeDefinitions](#)
- [BSEntityConfigDefaults](#)
- [BSEntityGetFullData](#)
- [BSEntitySetValuesByObject](#)

- [BSFoundationRendererMakeTagAttribs](#)
- [BSSocialEntityListInitialized](#)
- [BSSocialEntityOutputRenderAfterContent](#)
- [BSSocialEntityOutputRenderBeforeContent](#)
- [BSSocialModuleDepths](#)
- [SkinTemplateOutputPageBeforeExec](#)
- [TitleMoveComplete](#)

Entry fields for dialogs

Name	Description	Type	Default value
<i>tags</i>	Linked pages	array	Current page

Configuration

Name	Description	Type	Default	Scope
<i>bsg</i> SocialTagsTimelineAfterContentNamespaceBlackList	Determines in which namespaces the timeline is displayed below the page content with the current page as tag.	array	[]	LocalSettings.php
<i>bsg</i> SocialTagsTimelineAfterContentShow	Determines if the timeline is displayed below the page content with the current page as tag.	bool	false	LocalSettings.php