

Contents

1. Reference:Readers	2
2. Reference:BlueSpiceReaders	2

Reference:Readers

Redirect to:

- [Reference:BlueSpiceReaders](#)

Reference:BlueSpiceReaders

Extension\ BlueSpiceReaders

Overview			
Description:	Creates a list of the people who read a page		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-onlyProperty "BSExtensionInfoLicense" (as page type) with input value " GPL-3.0-only" contains invalid characters or is incomplete and therefore can cause unexpected results during a query or annotation process.
Type:	BlueSpice	Category:	Data Analysis
Edition:	BlueSpice free, BlueSpice pro, BlueSpice Farm, BlueSpice Cloud		
View help page			

Features

The extension **Readers** displays the readers of a wiki page to users with admin rights.

- Displays the readers of a page in the page information flyout of the page tools.
- The special page *Special:Readers/PageTitle* creates a list of all readers of a page along with the user name and the date of the last visit.

Wiki administrators can set the number of readers to be shown in the page information flyout in the [Config manager](#).

Technical Information

This information applies to BlueSpice 3 . Technical details for BlueSpice cloud can differ in some cases.

Requirements

MediaWiki: 1.31
BlueSpiceFoundation: 3.2

Integrates into

- BlueSpiceArticleInfo
- BlueSpicePrivacy

Special pages

- Readers
- RevisionReaders

Permissions

Name	Description	Role
viewreaders	View readers of a page	admin, maintenanceadmin
viewrevisionreaders	View readers of single page revisions	

Configuration

Name	Value
ReadersCleanData	false
ReadersCleanDataTTL	1095
ReadersNamespaceBlacklist	array (0 => 6, 1 => 7, 2 => 8, 3 => 9, 4 => 14, 5 => 15,)
ReadersNumOfReaders	10

API Modules

- bs-readers-data-store
- bs-readers-page-readers-store

- [bs-readers-revision-readers-store](#)
- [bs-readers-tasks](#)
- [bs-readers-users-store](#)

Hooks

- [BeforePageDisplay](#)
- [LoadExtensionSchemaUpdates](#)
- [SkinTemplateNavigation](#)
- [SkinTemplateOutputPageBeforeExec](#)