

## Contents

1. Setup:Installation Guide/Advanced/Performance Optimization/ManualRecache .....	2
2. Setup:Installation Guide/Advanced/Performance Optimization/PHP .....	2

## Setup:Installation Guide/Advanced/Performance Optimization /ManualRecache

A [quality version](#) of this page, [approved](#) on *29 November 2019*, was based off this revision.

To prevent Rebuilding LocalizationCache with every page call, apply the following configuration:



When following these instructions, make sure that the `$wgCacheDirectory` variable is set in advance. This is already the case in the BlueSpice standard delivery in the file `settings.d/005-Directories.php`.



This performance optimization achieves the best performance by enabling and configuring [opcache in PHP](#).

In the `settings.d` folder of your codebase, create the file `006-ManualRecache.php` with the following contents:

```
<?php
$wgLocalisationCacheConf = [
    'class' => LocalisationCache::class,
    'store' => 'array',
    'storeClass' => false,
    'storeDirectory' => $wgCacheDirectory,
    'manualRecache' => true,
];
```

Then delete all existing files in the `cache` folder of your codebase. Then manually re-create the LocalizationCache by entering the following on your console:

```
php /pfad/zur/installation/maintenance/rebuildLocalisationCache.php --force
```

Finally, make sure that this is done regularly in the background via cronjob ("Task Scheduler" under Windows). We recommend this twice a day, for example at 6am and 6pm.

### Performance Optimization: PHP

A [quality version](#) of this page, [approved](#) on *29 November 2019*, was based off this revision.

## Contents

1	<a href="#">opcache</a>	4
2	<a href="#">zlib</a>	4

## opcache

---

Enable the Zend extension opcache in PHP. In the php.ini, we recommend the following configuration:

```
opcache.enable=1
opcache.memory_consumption=512
opcache.max_accelerated_files=100000
opcache.validate_timestamps=1
opcache.revalidate_freq=2
opcache.optimization_level=0x7FFF9FFF
```

In addition, you should include the BlueSpice configuration files ( `extensions/BlueSpiceFoundation/config/*` ) in the Opcache blacklist ( `opcache.blacklist_filename` ). You can find more information in the [official PHP documentation](#) for configuration.php.

## zlib

---

Activate the extension zlib. In the php.ini we recommend the following configuration:

```
zlib.output_compression = 0n
zlib.output_compression_level = 9
```

You can find more information in the [official PHP documentation](#) for zlib.