Setup:Installation Guide/Upgrade free to pro



Contents

1.	Setup:Installation Guide/Upgrade free to pro	2
2.	Setup:Installation Guide/Patch Update	2



Setup:Installation Guide/Upgrade free to pro

A quality version of this page, approved on 2 August 2021, was based off this revision.

To upgrade from **BlueSpice free 3.x to BlueSpice pro 3.x** (under Linux), follow these instructions:

- 1. **Create backup:** Make a database dump and save it together with the complete codebase to another storage location.
- 2. **Patch-update BlueSpice free (optional):** Check your current version on the Special: Version page. Compare your version with the current version of BlueSpice free. If you have not installed a relatively current version, apply a patch update.
- 3. **Replace the codebase:** Overwrite the codebase of your current version with the new codebase of BlueSpice pro.
- 4. Start the update:
 - 1. Open a console and switch to he installation directory (the level of LocalSettings.php)
 - 2. Execute: php maintenance/update.php
- 5. Re-index the search:
 - Delete search index: php extensions/BlueSpiceExtendedSearch/maintenance/initbackends.
 - 2. Create new search index: php extensions/BlueSpiceExtendedSearch/maintenance /rebuildIndex.php --quick
 - 3. Run jobs: php maintenance/runJobs.php

Setup:Installation Guide/Patch Update

A quality version of this page, approved on 9 March 2021, was based off this revision.

For large version jumps (e.g., BlueSpice 2.27.3 to 3.1.10), a new installation is generally recommended.

For a patch update (for example, version 3.1.x to a higher version 3.1.x) you can simply follow these steps:

- 1. **Create a backup:** Pull a dump of the database and save it together with the complete codebase to a backup location of your choice.
- 2. **Renew the codebase:** Overwrite the codebase of the current version with the new codebase of the higher version.
- 3. **Compare**: After the overwrite, please compare the following files and folder. Copy from your backup location if necessary
 - 1. If you have a custom skin, please check the skins/ folder.
 - LocalSettings.php
 - 3. extensions/BlueSpiceFoundation/config
 - 4. settings.d/ In settings.d, especially *.local.php files. Copy from your backup if necessary.
- 4. Run the update:
 - 1. Open a console and go to the installation folder (on the LocalSettings.php level)
 - 2. Then enter the following command: php maintenance/update.php





If you use Linux as the basis of your BlueSpice installation, please note that file system permissions may be lost when overwriting the codebase. More information can be found under File System Permissions.

Note: In a patch update, usually no database schemas have changed. It may not be necessary to run update.php.