

Setup:Installation Guide/Webservices/VisualDiff

A [quality version](#) of this page, [approved](#) on *20 September 2019*, was based off this revision.

Contents

1 Tips for this Document	2
2 Copy of BShtmlDiff	2
3 Restart Tomcat	2
4 Troubleshooting	2

This document describes the installation of VisualDiff from BlueSpice. **VisualDiff is a exclusive component of BlueSpice pro!** Please note that the [Apache Tomcat server](#) must be installed and configured on the BlueSpice server.

Tips for this Document

- Please, read this manual completely and work through the single installation steps one after another.
- For editing the configuration files with a text editor, the files must be saved in UTF-8 coding without BOM (Byte Order Mark).
- The placeholder `<installpath-bluespice>` stands for the path to your BlueSpice installation, e.g. `C:\inetpub\wwwroot\bluespice` (Windows) or `/var/www/bluespice` (Linux).
- The placeholder `<tomcat-webapps>` stands for the path to the Webapps directory of your Tomcat server, e.g. `C:\Program Files\Apache Software Foundation\Tomcat 8.5\webapps` (Windows) or `/var/lib/tomcat8/webapps` (Linux).

Copy of BShtmlDiff

Move the file "BShtmlDiff.war" from the directory `<installpath-bluespice>/extensions/BlueSpiceVisualDiff/VisualDiff/webservices` to `<tomcat-webapps>`

Restart Tomcat

Restart the Tomcat Webserver.

This completes the installation of VisualDiff.

Troubleshooting

If there is a problem with VisualDiff in BlueSpice, first check the [file system permissions](#).